

1- Product Category: Recessed Light

2- Product Code: PVRS4-5CCT

3- Product Pictures:



4- Product Specifications :

- 4 inch 10w flat slim round panel light.
- 1/2 inch thick, fits in tight ceiling space.
- IC rated airtight recessed lights, for insulate ceiling.
- Suitable for damp,dry & wet locations.
- Fast & easy installation, can save labor cost.
- No recessed fixture required.
- 2700K/3000K/3500K/4000K/5000K Selectable.

 **4" 10W**
replaces up to 80W



About PVRS4-5CCT Flat Ultra-thin Slim Round Panel light

> 5 Color Temperature Dimmable

The led recessed lighting 4 inch fixture is dimmable, 2700K(Soft White), 3000K(Warm White), 3500K(Warm White),4000K(Warm White) ,5000K(Cool White). You can adjust the suitable color temperature for each location easily.

> High Brightness

90+CRI technology brings true color rendering to your job sites.

The PVRS4 use the new generation of LED chips with higher lumens and lower power.

700LM 1 Watts, which equals to 80W incandescent lamp, saving you up to 88% in energy costs.

> Easy Installation

Recessed lighting suitable for renovations and new installation. Each lights package which we deliver has a detailed manual. LED recessed light 4 inch with junction box, you only need to cut a suitable hole in the ceiling, fix its size, and then fold the spring support upwards and push it up into the hole. It can be done in a few minutes, and the installation is easy going.

> Wide Application

Thin slim LED panel light 4 inch, not afraid of all kinds of environment.

Seamless dimming capabilities(5%-100%) to fit indoor any scene.

With the attached junction box, the rated value of the insulating contacts can be directly in contact with the insulation. Wet location can lights for ceiling are ideal for bathrooms.

Maximum Safety

The slim panel light 4 inch has been certified to ETL & Energy Star high standards.

Our factory provides a five-year warranty. If you have any orders or questions you can contact us via the following form, we will provide you with the best pre-sales & after-sales service.

Dimension



5- Product Installation :

Easy Installation

No can needed



- Step 1:
Cut a 4.1"- 4.3" hole in the ceiling
- Step 2:
Connect wires with wire nuts
- Step 3:
Connect the fixture with the hardwire box
- Step 4:
Push the spring-loaded clips upwards and fix the fixture

6- Product Application

