



PICOVOLT

# in Ground Lights



## PVG 42-1W

### PVG 42 - 1W - LED Lamp

<b>Input Voltage</b>	DC 12V
<b>IP Grade</b>	IP67
<b>Cover</b>	SS304 Stainless Steel
<b>Body Material</b>	ABS Plastic Fixing box
<b>Chip</b>	Bridgelux 1W
<b>Dimensions</b>	42 * 73 mm
<b>Color Temperature</b>	3000k, 4000K



## PVG 85 - 3W

### PVG 85 - 3W - LED Lamp

<b>Input Voltage</b>	DC 12V
<b>IP Grade</b>	IP67
<b>Cover</b>	SS304 Stainless Steel
<b>Body Material</b>	ABS Plastic Fixing box
<b>Chip</b>	Epister 3W
<b>Dimensions</b>	D80 * H105 mm
<b>Color Temperature</b>	3000K, 4000K



## PVG 210 - 10W

### PVG 210 -10W- LED Lamp

<b>Input Voltage</b>	DC 12V
<b>IP Grade</b>	IP67
<b>Cover</b>	SS304 Stainless Steel
<b>Body Material</b>	ABS Plastic Fixing box
<b>Chip</b>	Bridgelux 10W
<b>Dimensions</b>	D210 * H120 mm
<b>Hole Size</b>	D195 * H125 mm
<b>Color Temperture</b>	3000K, 4000K



## PVG 130 - 5W

### PVG 130 - 5W - LED Lamp

<b>Input Voltage</b>	DC 12V
<b>IP Grade</b>	IP67
<b>Cover</b>	SS304 Stainless Steel
<b>Body Material</b>	ABS Plastic fixing box
<b>Chip</b>	Bridgelux 5W
<b>Dimensions</b>	D130 * H98 mm
<b>Hole Size</b>	D120 * H105 mm
<b>Color Temperture</b>	3000K, 4000K



## PVG 73C - 3W

### PVG 73C - 3W - LED Lamp

<b>Input Voltage</b>	DC 12V
<b>IP Grade</b>	IP67
<b>Cover</b>	SS304 Stainless Steel
<b>Body Material</b>	ABS Plastic fixing box
<b>Chip</b>	Bridgelux 3W
<b>Dimensions</b>	D73 * H98 mm
<b>Hole Size</b>	D68 * H100 mm
<b>Color Temperture</b>	3000k , 4000k



PICOVOLT

# Garden Spot Lights



## PVGA 0904-9W

### PVGA 0904 - 9W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP67
Body Material	Aluminium
Cover	Tempered Glass
Chip	Epistar 9 LED
Dimensions	140mm * 100mm * 155mm 30-50mm Wire Line
Color Temperature	Cool White 6000 - 6500K

## PVGA 1204-12W - RGB

### PVGA 1204 - 12W - RGB - LED Lamp

Input Voltage	DC 12V
IP Grade	IP67
Body Material	Aluminium
Cover	Tempered Glass
Chip	Epistar COB
Dimensions	68mm * 78mm * 155mm 30 - 50mm Wire Line
Color Temperature	Warm White 2700 - 3200K, RGB



## PVGA 1804 - 18W

### PVGA 1804 - 18W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP67
Body Material	Aluminium
Cover	Tempered Glass
Chip	Epistar COB
Dimensions	160mm * 90mm * 155mm 30-50mm Wire Line
Color Temperature	Warm White 2700-3200K

## PVGA-GL12-12W

### PVGA-GL12-12W - COB Lamp

Input Voltage	DC 12V
IP Grade	IP65
Body Material	Aluminium
Cover	Tempered Glass
Chip	Epistar COB
Dimensions	98mm*115mm*155mm 30 - 50mm Wire Line
Color Temperature	Warm White 2700-3200K, Day White 4000 - 4500K



PICOVOLT

# Stair Lights



## PVS 9F - 3W

### PVS 9F - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP54
Body Material	Aluminium
LED	Bridgelux
Dimensions	85 * 50 * 29 mm
Hole Size	65 mm
Color	White
Color Temperature	3000K, 4000K



## PVS 4F - 3W

### PVS 4F - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP54
Body Material	Aluminium
LED	Bridgelux
Dimensions	55 * 55 * 29 mm
Hole Size	45 mm
Color	White, Black
Color Temperature	3000K, 4000K



## PVS 4R - 3W

### PVS 4R - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP54
Body Material	Aluminium
LED	Bridgelux
Dimensions	55 * 29 mm
Hole Size	45 mm
Color	White, Black
Color Temperature	3000K, 4000K



PICOVOLT

# Under Cabinet Lamps



## PVA 1024 - 3W

### PVA 1024 - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP20
Body Material	Aluminium
LED	COB LED Chip
Dimensions/Hole Size	D60, H40mm / 42 mm
Color	White, Black
Color Temperature	3000K, 6000K



## PVA 1033 - 3W

### PVA 1033- 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP20
Body Material	Aluminium
LED	COB LED Chip
Dimensions/Hole Size	D60, H20 mm / 42 mm
Color	White, Black, Silver
Color Temperature	3000K, 4000K, 6000K



## PVA 1030 - 3W

### PVA 1030 - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP20
Body Material	Aluminium
LED	COB LED Chip
Dimensions/Hole Size	D60, H40 mm / 42 mm
Color	White, Black, Silver
Color Temperature	3000K, 6000K



PICOVOLT

# Under Cabinet Lamps



## PVA 1554 - 3W

### PVA 1554 - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP20
Body Material	Aluminium
LED	COB LED Chip
Dimensions/Hole Size	D68, H50, L25 mm / 50 mm
Color	White, Black, Silver
Color Temperature	3000K, 6000K



## PVA 1621 - 3W

### PVA 1621 - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP20
Body Material	Aluminium
LED	COB LED Chip
Dimensions/Hole Size	D35, H45 / 28 mm
Color	White, Black
Color Temperature	3000K



## PVA 1639 - 3W

### PVA 1639 - 3W - LED Lamp

Input Voltage	DC 12V
IP Grade	IP20
Body Material	Aluminium
LED	CREE LED Chip
Dimensions	25 * 80 mm
Color	Silver
Color Temperature	3000K



PICOVOLT

# Wall Lights



## PVW-101 E26 - 60W

### PVW-101 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP54
Body Material	Aluminium, Die Casting-Body, Tempering Glass Deffuser
Light Source	Maximum 60W, E26 Lamp
Certification	CE, RoHs, <b>ETL</b>
Dimensions	108 * 147 * 180 mm
Color	Black, Bronze



## PVW-102 E26 - 60W

### PVW-102 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP54
Body Material	Aluminium, Die Casting-Body, Tempering Glass Deffuser
Light Source	Maximum 60W, E26 Lamp
Certification	CE, RoHs, <b>ETL</b>
Dimensions	108 * 147 * 260 mm
Color	Black, Bronze



## PVW-103 E26 - 60W

### PVW-103 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP54
Body Material	Aluminium, Die Casting-Body, Tempering Glass Deffuser
Light Source	Maximum 60W, E26 Lamp
Certification	CE - RoHs - <b>ETL</b>
Dimensions	108 * 175 * 300 mm
Color	Black, White



## PVW-104 E26 - 60W

### PVW-104 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP54
Body Material	Aluminium, Die Casting-Body, Tempering Glass Deffuser
Light Source	Maximum 60W, E26 Lamp
Certification	CE, RoHs, <b>ETL</b>
Dimensions	108 * 147 * 200 mm
Color	Black

2 Years Warranty



PICOVOLT

# Wall Lights



## PVW-117 E26 - 60W

### PVW-117 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP54
Body Material	Aluminium, Die Casting Body, Tempering Glass Deffiuser
Light Source	2 * Maximum 60W, E26 Lamp
Certification	CE, RoHs, <b>ETL</b>
Dimensions	108 * 175 * 320 mm
Color	Black

## PVW-108 E26 - 60W

### PVW-108 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP54
Body Material	Aluminium, Die Casting-Body, Tempering Glass Deffiuser
Light Source	Maximum 60W, E26 Lamp
Certification	CE, RoHs, <b>ETL</b>
Dimensions	108 * 175 * 210 mm
Color	Black



## PVW-K4401 E26- 60W

### PVW-K4401 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP44
Body Material	Aluminium, Lamp Body, Clear Glass
Certification	CE, RoHs, <b>ETL</b>
Dimensions	160 * 190 * 420 mm
Color	Black, Brown

## PVW-K4801 E26- 60W

### PVW-K4801 E26 - 60W - LED Lamp

Input Voltage	100-240V, 50/60Hz
IP Grade	IP44
Body Material	Aluminium, Lamp Body, Clear Glass
Certification	CE, RoHs, <b>ETL</b>
Dimensions	205 * 245 * 445 mm
Color	Black, Brown

2 Years Warranty



PICOVOLT

# Minilight Down Light



## PVD2 - 1W

### PVD2 - 1W - LED Lamp

<b>Input Voltage</b>	DC12V
<b>Body Material</b>	Aluminium, Pmma
<b>Dimensions/Cut Size</b>	33 * 28 mm / 025 mm
<b>Color Temperature</b>	3000K

## PVD3 - 1W

### PVD3 - 1W - LED Lamp

<b>Input Voltage</b>	DC12V
<b>Body Material</b>	Aluminium, Pmma
<b>Dimensions/Cut Size</b>	33 * 30 mm / 025 mm
<b>Color Temperature</b>	6000K



## PVD4 - 1W

### PVD4 - 1W - LED Lamp

<b>Input Voltage</b>	DC12V
<b>Body Material</b>	Aluminium, Crystal
<b>Dimensions/Cut Size</b>	44 * 40 mm / 40mm
<b>Color Temperature</b>	3000K

## PVD5 - 3W

### PVD5 - 3W - LED Lamp

<b>Input Voltage</b>	DC12V
<b>Body Material</b>	Aluminium, Crystal
<b>LED</b>	COB 3w
<b>Dimensions/Cut Size</b>	33 * 37 mm / 25mm
<b>Color Temperature</b>	3000K, 6000K

## PVD15R - 1W

### PVD15R - 1W - LED Lamp

<b>Input Voltage</b>	DC12V
<b>Body Material</b>	Aluminium
<b>LED</b>	COB 3W
<b>Dimensions/Cut Size</b>	38 * 25 mm / 30 mm
<b>Color Temperature</b>	3000K, 6000K





PICOVOLT

# Mini down light



## PVD8F-3W



### PVD8F - 3W - LED Lamp

Input Voltage	DC12V
Body Material	Aluminium
LED	COB 3W
Dimensions	38 * 38 * 45 mm
Colors	White, Black
Color Temperature	3000K, 6000K

## PVD8R-3W

### PVD8R - 3W - LED Lamp

Input Voltage	DC12V
Body Material	Aluminium
LED	COB 3W
Dimensions	38 * 45 mm
Colors	White, Black
Color Temperature	3000K, 6000K



## PVD9F-3W

### PVD9F - 3W - LED Lamp

Input Voltage	DC12V
Body Material	Aluminium
LED	COB 3W
Dimensions / Cut Size	38 * 38 * 51 mm / 30mm
Colors	Black
Color Temperature	3000K

## PVD9R-3W


### PVD9R - 3W - LED Lamp

Input Voltage	DC12V
Body Material	Aluminium
LED	COB 3W
Dimensions / Cut Size	35 * 47 mm / 30mm
Colors	White, Black
Color Temperature	3000K



PICOVOLT

# LED Strips



## PVST 3014 - 60 LED

### PVST 3014 - 60 LED

Input Voltage	24 V
IP Grade	IP67, IP20
PCB Width	10 mm
Rate Power Watt/M	6 W/M
Color K	3000k, 4000K, 6000K
Packing Roll	5 M, 10 M, 15 M



## PVST 3014 - 120 LED

### PVST 3014 - 120 LED

Input Voltage	24 V
IP Grade	IP68, IP20
PCB Width	8mm
Rate Power Watt/M	12 W/M
Color K	3000k, 4000K, 6000K
Packing Roll	5 M, 10 M, 15 M



## PVST 3528 - 60 LED

### PVST 3528 - 60 LED

Input Voltage	24 V
IP Grade	IP68, IP20
PCB Width	8mm
Rate Power Watt/M	4.8 W/M
Color K	3000k, 4000K, 6000K
Packing Roll	5 M, 10 M, 15 M

## PVST 3528 - 180 LED

### PVST 3528 - 180 LED

Input Voltage	24 V
IP Grade	IP68, IP20
PCB Width	8mm
Rate Power Watt/M	14.4 W/M
Color K	3000k, 4000K, 6000K , RGB
Packing Roll	5 M, 10 M, 15 M

## PVST ACT31 RGB Controller

### Mini Bluetooth RGB